

TEFCOLD[®]



2019-2020



TEFCOLD UDRS7-P

Premium ice cream freezer with a modern and elegant look.
With curved glass guard the ice cream is under optimized hygienic conditions.

Scoop Ice Cream Freezers



Layout based on 5L Napoli pans



UDRS9-P

Scoop Ice Cream Freezer

- Open ice cream freezer for scoop ice
- Sneeze guard in curved glass
- Suitable for Napoli Pans (not included)
- Lift up rear lid (2 can serve)
- LED interior light
- Easy access storage compartment
- Automatic defrost
- Optional - Rear shelf with scoop wash



Suitable for Napoli Pans
(accessory)



Easy access storage
compartment



UDRS10-P

Scoop Ice Cream Freezer

- Open ice cream freezer for scoop ice
- Sneeze guard in angled glass
- Suitable for Napoli Pans (not included)
- Flat sliding lids
- LED interior light
- Easy access storage compartment
- Castors with brake

UDRS7-P

Scoop Ice Cream Freezer

- Open ice cream freezer for scoop ice
- Sneeze guard in curved glass
- Suitable for Napoli Pans (not included)
- Easy access storage compartment
- Lift up rear lid (2 can serve)
- LED interior light
- Automatic defrost
- Optional - Rear shelf with scoop wash


MODEL		UDRS10-P	UDRS7-P	UDRS9-P
Gross / Net Volume	l	431 / 342	317 / 264	423 / 357
Gross / Net Weight	kg	112 / 103	119 / 98	131 / 110
Climate Class		4	4	4
Temperature Range	°C	-20 to -14	-20 to -14	-20 to -14
Lid Number & Type		2 flat sliding temp. glass lids	1 transparent acrylic lid	1 transparent acrylic lid
Basket Number & Type		-	-	-
Interior Light		No	LED	LED
Castors		4 double castors	4 double castors	4 double castors
Exterior Finish		White	White	White
Interior Finish		White painted steel	White painted steel	White painted steel
Thermometer		Yes	Yes	Yes
Type of Controller		Mechanical	Electronic	Electronic
Noise Level	db(A)	45	45	45
Type of Cooling		Static	Static	Static
Type of Defrost		Manual	Automatic	Automatic
Refrigerant		R290	R290	R290
Refrigerant Charge	g	100	130	150
Input Power	W	360	500	540
Voltage / Frequency	V/Hz	220-240/50	220-240/50	220-240/50
Energy Consumption	kWh/24h	3,5	7,75	9
Internal Dimension (WxDxH)	mm	1217 x 563 x 295	1217 x 450 x 240	1532 x 450 x 240
External Dimension (WxDxH)	mm	1341 x 725 x 1235	1341 x 723 x 1212	1656 x 723 x 1212
Packed Dimension (WxDxH)	mm	1385 x 730 x 1020	1420 x 760 x 1310	1735 x 760 x 1310
40ft Container Load	pcs	56	24	20

Scoop Ice Cream Freezers



Storage based on 5L plastic tubs

Layout based on 5L Napoli pans



IC400SC-P-SO

Scoop Ice Cream Freezer


- Sneeze guard in curved glass
- Flat sliding lids with lock
- Scooping basket option
- Storage under baskets
- Castors with brake
- Powder coated white steel inner liner



Scooping basket option



Scoop wash option



IC200SC-I-SO Scoop Ice Cream Freezer

- Sneeze guard in curved glass
- Flat sliding lids with lock
- Scooping basket option
- Storage under baskets
- Castors with brake
- Powder coated white steel inner liner

IC300SC-P-SO Scoop Ice Cream Freezer

- Sneeze guard in curved glass
- Flat sliding lids with lock
- Scooping basket option
- Storage under baskets
- Castors with brake
- Powder coated white steel inner liner


MODEL	IC200SC-I-SO	IC300SC-P-SO	IC400SC-P-SO
Gross / Net Volume	l 191 / 165	296 / 255	401 / 350
Gross / Net Weight	kg 75 / 70	91 / 82	100 / 90
Climate Class	5	5	5
Temperature Range	°C -24 to -14	-24 to -14	-24 to -14
Lid Number & Type	2 flat sliding temp. glass lids	2 flat sliding temp. glass lids	2 flat sliding temp. glass lids
Basket Number & Type	Additional (see drawings)	Additional (see drawings)	Additional (see drawings)
Castors	4 wheels, 2 with brake	4 wheels, 2 with brake	4 wheels, 2 with brake
Exterior Finish	White	White	White
Interior Finish	White painted steel	White painted steel	White painted steel
Lock	Yes	Yes	Yes
Thermometer	Yes	Yes	Yes
Type of Controller	Mechanical	Mechanical	Mechanical
Noise Level	db(A) 45	45	45
Type of Cooling	Static	Static	Static
Type of Defrost	Manual	Manual	Manual
Refrigerant	R600a	R290	R290
Refrigerant Charge	g 55	85	105
Input Power	W 98	119	141
Voltage / Frequency	V/Hz 220-240/50	220-240/50	220-240/50
Energy Consumption	kWh/24h 1,32	1,48	1,93
Internal Dimension (WxDxH)	mm 600 x 510 x 655	890 x 510 x 655	1180 x 510 x 655
External Dimension (WxDxH)	mm 720 x 630 x 1250	1010 x 630 x 1250	1300 x 630 x 1250
Packed Dimension (WxDxH)	mm 800 x 750 x 1130	1100 x 750 x 1130	1400 x 750 x 1130
40ft Container Load	pcs 92	64	50

Scoop Ice Cream Freezers



Storage based on 5L plastic tubs

Layout based on 5L Napoli pans



IC400SCE-P-SO

Scoop Ice Cream Freezer


- Sneeze guard in curved glass
- Angled sliding lids with lock
- Scooping basket option
- Storage under baskets
- Castors with brake
- Powder coated white steel inner liner



Scooping basket option



Scoop wash option



IC200SCE-I-SO Scoop Ice Cream Freezer

- Sneeze guard in curved glass
- Angled sliding lids with lock
- Scooping basket option
- Storage under baskets
- Castors with brake
- Powder coated white steel inner liner

IC300SCE-P-SO Scoop Ice Cream Freezer

- Sneeze guard in curved glass
- Angled sliding lids with lock
- Scooping basket option
- Storage under baskets
- Castors with brake
- Powder coated white steel inner liner

MODEL	IC200SCE-I-SO	IC300SCE-P-SO	IC400SCE-P-SO
Gross / Net Volume	l 176 / 157	264 / 230	352 / 325
Gross / Net Weight	kg 76 / 69	89 / 76	102 / 92
Climate Class	5	5	5
Temperature Range	°C -24 to -14	-24 to -14	-24 to -14
Lid Number & Type	2 flat angled sliding temp. glass lids	2 flat angled sliding temp. glass lids	2 flat angled sliding temp. glass lids
Basket Number & Type	Additional (see drawings)	Additional (see drawings)	Additional (see drawings)
Castors	4 wheels, 2 with brake	4 wheels, 2 with brake	4 wheels, 2 with brake
Exterior Finish	White	White	White
Interior Finish	White painted steel	White painted steel	White painted steel
Lock	Yes	Yes	Yes
Thermometer	Yes	Yes	Yes
Type of Controller	Mechanical	Mechanical	Mechanical
Noise Level	db(A) 45	45	45
Type of Cooling	Static	Static	Static
Type of Defrost	Manual	Manual	Manual
Refrigerant	R600a	R290	R290
Refrigerant Charge	g 55	85	105
Input Power	W 98	119	141
Voltage / Frequency	V/Hz 220-240/50	220-240/50	220-240/50
Energy Consumption	kWh/24h 1,32	1,48	1,93
Internal Dimension (WxDxH)	mm 600 x 495 x 710	890 x 495 x 710	1180 x 495 x 710
External Dimension (WxDxH)	mm 720 x 615 x 1295	1010 x 615 x 1295	1300 x 615 x 1295
Packed Dimension (WxDxH)	mm 800 x 750 x 1200	1100 x 750 x 1200	1400 x 750 x 1200
40ft Container Load	pcs 92	64	50

Ice Cream Freezers



IC300SCE-P

Ice Cream Freezer

- Angled sliding lids with lock
- Thermometer
- Powder coated white steel inner liner
- Basket
- Castors with brake



Castors with and without brake



Illuminated display board as option (accessory)



IC100SCE-I Ice Cream Freezer

- Angled sliding lids with lock
- Thermometer
- Powder coated white steel inner liner
- Basket
- Castors with brake



IC200SCE-I Ice Cream Freezer

- Angled sliding lids with lock
- Thermometer
- Powder coated white steel inner liner
- Basket
- Castors with brake

MODEL		IC100SCE-I	IC200SCE-I	IC300SCE-P
Gross / Net Volume	l	100 / 85	176 / 157	264 / 230
Gross / Net Weight	kg	40 / 37	58 / 53	65 / 57
Climate Class		5	5	5
Temperature Range	°C	-24 to -14	-24 to -14	-24 to -14
Lid Number & Type		2 flat angled sliding temp. glass lids	2 flat angled sliding temp. glass lids	2 flat angled sliding temp. glass lids
Basket Number & Type		1 Wire basket, white	1 Wire basket, white	1 Wire basket, white
Castors		4 double castors	4 wheels, 2 with brake	4 wheels, 2 with brake
Exterior Finish		White	White	White
Interior Finish		White painted steel	White painted steel	White painted steel
Lock		Yes	Yes	Yes
Thermometer		Yes	Yes	Yes
Type of Controller		Mechanical	Mechanical	Mechanical
Noise Level	db(A)	45	45	45
Type of Cooling		Static	Static	Static
Type of Defrost		Manual	Manual	Manual
Refrigerant		R600a	R600a	R290
Refrigerant Charge	g	60	55	85
Input Power	W	80	98	119
Voltage / Frequency	V/Hz	220-240/50	220-240/50	220-240/50
Energy Consumption	kWh/24h	1	1,32	1,48
Internal Dimension (WxDxH)	mm	450 x 450 x 490	600 x 495 x 710	890 x 495 x 710
External Dimension (WxDxH)	mm	570 x 570 x 855	720 x 615 x 949	1010 x 615 x 949
Packed Dimension (WxDxH)	mm	680 x 700 x 1010	800 x 750 x 1010	1100 x 750 x 1010
40ft Container Load	pcs	108	92	64

Ice Cream Freezers



IC500SCE-P

Ice Cream Freezer

- Angled sliding lids with lock
- Thermometer
- Powder coated white steel inner liner
- Baskets
- Castors with brake



Castors with and without brake



Illuminated display board as option (accessory)



IC400SCE-P

Ice Cream Freezer

- Angled sliding lids with lock
- Thermometer
- Powder coated white steel inner liner
- Baskets
- Castors with brake

DID YOU KNOW?

We do not compromise with the quality of our products, but aim to deliver products, which function under the toughest conditions

MODEL	IC400SCE-P	IC500SCE-P
Gross / Net Volume	l 352 / 325	427 / 398
Gross / Net Weight	kg 76 / 66	82 / 72
Climate Class	5	5
Temperature Range	°C -24 to -14	-24 to -14
Lid Number & Type	2 flat angled sliding temp. glass lids	2 flat angled sliding temp. glass lids
Basket Number & Type	2 Wire baskets, white	2 Wire basket, white
Castors	4 wheels, 2 with brake	4 wheels, 2 with brake
Exterior Finish	White	White
Interior Finish	White painted steel	White painted steel
Lock	Yes	Yes
Thermometer	Yes	Yes
Type of Controller	Mechanical	Mechanical
Noise Level	db(A) 45	45
Type of Cooling	Static	Static
Type of Defrost	Manual	Manual
Refrigerant	R290	R290
Refrigerant Charge	g 105	110
Input Power	W 141	191
Voltage / Frequency	V/Hz 220-240/50	220-240/50
Energy Consumption	kWh/24h 1,93	2,39
Internal Dimension (WxDxH)	mm 1180 x 495 x 710	1420 x 495 x 710
External Dimension (WxDxH)	mm 1300 x 615 x 949	1550 x 615 x 949
Packed Dimension (WxDxH)	mm 1400 x 750 x 1010	1640 x 750 x 1010
40ft Container Load	pcs 50	42

Ice Cream Freezers



IC300SC-P

Ice Cream Freezer

- Flat sliding lids with lock
- Thermometer
- Powder coated white steel inner liner
- Basket
- Castors with brake



Castors with and without brake



Illuminated display board as option (accessory)



IC100SC-I Ice Cream Freezer

- Flat sliding lids with lock
- Thermometer
- Powder coated white steel inner liner
- Basket
- Castors with brake



IC200SC-I Ice Cream Freezer

- Flat sliding lids with lock
- Thermometer
- Powder coated white steel inner liner
- Basket
- Castors with brake

MODEL		IC100SC-I	IC200SC-I	IC300SC-P
Gross / Net Volume	l	108 / 91	191 / 165	296 / 255
Gross / Net Weight	kg	47 / 42	57 / 52	67 / 62
Climate Class		5	5	5
Temperature Range	°C	-24 to -14	-24 to -14	-24 to -14
Lid Number & Type		2 flat sliding temp. glass lids	2 flat sliding temp. glass lids	2 flat sliding temp. glass lids
Basket Number & Type		1 Wire basket, white	1 Wire basket, white	1 Wire basket, white
Castors		4 double castors	4 wheels, 2 with brake	4 wheels, 2 with brake
Exterior Finish		White	White	White
Interior Finish		White painted steel	White painted steel	White painted steel
Lock		Yes	Yes	Yes
Thermometer		Yes	Yes	Yes
Type of Controller		Mechanical	Mechanical	Mechanical
Noise Level	db(A)	45	45	45
Type of Cooling		Static	Static	Static
Type of Defrost		Manual	Manual	Manual
Refrigerant		R600a	R600a	R290
Refrigerant Charge	g	60	55	85
Input Power	W	80	98	119
Voltage / Frequency	V/Hz	220-240/50	220-240/50	220-240/50
Energy Consumption	kWh/24h	1	1,32	1,48
Internal Dimension (WxDxH)	mm	450 x 450 x 520	600 x 510 x 655	890 x 510 x 655
External Dimension (WxDxH)	mm	570 x 570 x 855	720 x 630 x 892	1010 x 630 x 892
Packed Dimension (WxDxH)	mm	680 x 700 x 950	800 x 750 x 940	1100 x 750 x 940
40ft Container Load	pcs	108	92	64

Ice Cream Freezers



IC700SC-P

Ice Cream Freezer

- Flat sliding lids with lock
- Thermometer
- Powder coated white steel inner liner
- Baskets
- Castors with brake



Castors with and without brake



Illuminated display board as option (accessory)



IC400SC-P Ice Cream Freezer

- Flat sliding lids with lock
- Thermometer
- Powder coated white steel inner liner
- Baskets
- Castors with brake



IC500SC-P Ice Cream Freezer

- Flat sliding lids with lock
- Thermometer
- Powder coated white steel inner liner
- Baskets
- Castors with brake

MODEL		IC400SC-P	IC500SC-P	IC550SC-P	IC700SC-P
Gross / Net Volume	l	401 / 350	491 / 430	555 / 486	670 / 620
Gross / Net Weight	kg	82 / 77	98 / 93	114 / 96	115 / 100
Climate Class		5	5	5	5
Temperature Range	°C	-24 to -14	-24 to -14	-24 to -14	-24 to -14
Lid Number & Type		2 flat sliding temp. glass lids	2 flat sliding temp. glass lids	2 flat sliding temp. glass lids	2 flat sliding temp. glass lids
Basket Number & Type		2 Wire baskets, white	2 Wire baskets, white	2 Wire baskets, white	3 Wire baskets, white
Castors		4 wheels, 2 with brake	4 wheels, 2 with brake	4 wheels, 2 with brake	4 wheels, 2 with brake
Exterior Finish		White	White	White	White
Interior Finish		White painted steel	White painted steel	White painted steel	White painted steel
Lock		Yes	Yes	Yes	Yes
Thermometer		Yes	Yes	Yes	Yes
Type of Controller		Mechanical	Mechanical	Mechanical	Mechanical
Noise Level	db(A)	45	45	45	45
Type of Cooling		Static	Static	Static	Static
Type of Defrost		Manual	Manual	Manual	Manual
Refrigerant		R290	R290	R290	R290
Refrigerant Charge	g	105	110	120	125
Input Power	W	141	191	273	292
Voltage / Frequency	V/Hz	220-240/50	220-240/50	220-240/50	220-240/50
Energy Consumption	kWh/24h	1,93	2,39	3,49	3,57
Internal Dimension (WxDxH)	mm	1180 x 510 x 655	1430 x 510 x 655	1630 x 510 x 655	1930 x 510 x 655
External Dimension (WxDxH)	mm	1300 x 630 x 892	1550 x 630 x 892	1750 x 630 x 892	2055 x 630 x 892
Packed Dimension (WxDxH)	mm	1400 x 750 x 940	1640 x 750 x 940	1850 x 750 x 940	2100 x 750 x 940
40ft Container Load	pcs	50	42	38	32

Ice Cream Freezers



IC550SCEB-P

Ice Cream Freezer

- Curved sliding lids with lock
- Thermometer
- Powder coated white steel inner liner
- Baskets
- Castors with brake



Castors with and without brake



Illuminated display board as option (accessory)



IC400SCEB-P Ice Cream Freezer

- Curved sliding lids with lock
- Thermometer
- Powder coated white steel inner liner
- Baskets
- Castors with brake



IC500SCEB-P Ice Cream Freezer

- Curved sliding lids with lock
- Thermometer
- Powder coated white steel inner liner
- Baskets
- Castors with brake

MODEL		IC400SCEB-P	IC500SCEB-P	IC550SCEB-P
Gross / Net Volume	l	352 / 325	427 / 398	540 / 481
Gross / Net Weight	kg	76 / 66	82 / 72	114 / 96
Climate Class		5	5	5
Temperature Range	°C	-24 to -14	-24 to -14	-24 to -14
Lid Number & Type		2 curved sliding temp. glass lids	2 curved sliding temp. glass lids	2 curved sliding temp. glass lids
Basket Number & Type		2 Wire baskets, white	2 Wire baskets, white	2 Wire baskets, white
Castors		4 wheels, 2 with brake	4 wheels, 2 with brake	4 wheels, 2 with brake
Exterior Finish		White	White	White
Interior Finish		White painted steel	White painted steel	White painted steel
Lock		Yes	Yes	Yes
Thermometer		Yes	Yes	Yes
Type of Controller		Mechanical	Mechanical	Mechanical
Noise Level	db(A)	45	45	45
Type of Cooling		Static	Static	Static
Type of Defrost		Manual	Manual	Manual
Refrigerant		R290	R290	R290
Refrigerant Charge	g	105	110	120
Input Power	W	141	191	292
Voltage / Frequency	V/Hz	220-240/50	220-240/50	220-240/50
Energy Consumption	kWh/24h	1,93	2,39	3,45
Internal Dimension (WxDxH)	mm	1180 x 495 x 710	1420 x 495 x 710	1650 x 495 x 710
External Dimension (WxDxH)	mm	1300 x 615 x 949	1550 x 615 x 949	1750 x 615 x 949
Packed Dimension (WxDxH)	mm	1400 x 750 x 1010	1640 x 750 x 1010	1840 x 750 x 1010
40ft Container Load	pcs	50	42	38

Ice Cream Freezers



IC300SCEB-P

Ice Cream Freezer

- Curved sliding lids with lock
- Thermometer
- Powder coated white steel inner liner
- Basket
- Castors with brake



Castors with and without brake



Illuminated display board as option (accessory)



IC100SCEB-I LED Ice Cream Freezer

- Curved sliding lids with lock
- Thermometer
- Powder coated white steel inner liner
- Basket
- Castors with brake



IC200SCEB-I Ice Cream Freezer

- Curved sliding lids with lock
- Thermometer
- Powder coated white steel inner liner
- Basket
- Castors with brake

MODEL		IC100SCEB-I	IC100SCEB-I LED	IC200SCEB-I	IC300SCEB-P
Gross / Net Volume	l	100 / 85	100 / 85	176 / 157	264 / 230
Gross / Net Weight	kg	40 / 37	40 / 37	58 / 53	65 / 57
Climate Class		5	5	5	5
Temperature Range	°C	-24 to -14	-24 to -14	-24 to -14	-24 to -14
Lid Number & Type		2 curved sliding temp. glass lids	2 curved sliding temp. glass lids	2 curved sliding temp. glass lids	2 curved sliding temp. glass lids
Basket Number & Type		1 Wire basket, white	1 Wire basket	1 Wire basket, white	1 Wire basket, white
Interior Light		No	LED Cold white	No	No
Castors		4 double castors	4 double castors	4 wheels, 2 with brake	4 wheels, 2 with brake
Exterior Finish		White	White	White	White
Interior Finish		White painted steel	White painted steel	White painted steel	White painted steel
Lock		Yes	Yes	Yes	Yes
Thermometer		Yes	Yes	Yes	Yes
Type of Controller		Mechanical	Mechanical	Mechanical	Mechanical
Noise Level	db(A)	45	45	45	45
Type of Cooling		Static	Static	Static	Static
Type of Defrost		Manual	Manual	Manual	Manual
Refrigerant		R600a	R600a	R600a	R290
Refrigerant Charge	g	60	60	55	85
Input Power	W	80	80	98	119
Voltage / Frequency	V/Hz	220-240/50	220-240/50	220-240/50	220-240/50
Energy Consumption	kWh/24h	1	1	1,32	1,48
Internal Dimension (WxDxH)	mm	450 x 450 x 490	450 x 450 x 490	600 x 495 x 710	890 x 495 x 710
External Dimension (WxDxH)	mm	570 x 570 x 885	570 x 570 x 885	720 x 615 x 949	1010 x 615 x 949
Packed Dimension (WxDxH)	mm	680 x 700 x 1010	680 x 700 x 1010	800 x 750 x 1010	1100 x 750 x 1010
40ft Container Load	pcs	108	108	92	64


Ice Cream Freezers



NIC500SC-P

Ice Cream Freezer

- Flat sliding lids with lock
- Digital thermometer
- Powder coated white steel inner liner
- Baskets
- Castors with brake



White coated steel inner liner



Digital thermometer



NIC200SC-I Ice Cream Freezer

- Flat sliding lids with lock
- Digital thermometer
- Powder coated white steel inner liner
- Basket
- Castors with brake



NIC300SC-P Ice Cream Freezer

- Flat sliding lids with lock
- Digital thermometer
- Powder coated white steel inner liner
- Basket
- Castors with brake

MODEL		NIC200SC-I	NIC300SC-P	NIC400SC-P	NIC500SC-P
Gross / Net Volume	l	186 / 138	288 / 218	390 / 298	478 / 367
Gross / Net Weight	kg	63 / 52	70 / 62	87 / 72	122 / 110
Climate Class		5	5	5	5
Temperature Range	°C	-24 to -14	-24 to -14	-24 to -14	-24 to -14
Lid Number & Type		2 flat sliding temp. glass lids	2 flat sliding temp. glass lids	2 flat sliding temp. glass lids	2 flat sliding temp. glass lids
Basket Number & Type		1 Wire basket, white	1 Wire basket, white	2 Wire basket, white	2 Wire basket, white
Castors		4 wheels, 2 with brake	4 wheels, 2 with brake	4 wheels, 2 with brake	4 wheels, 2 with brake
Exterior Finish		White	White	White	White
Interior Finish		White painted steel	White painted steel	White painted steel	White painted steel
Lock		Yes	Yes	Yes	Yes
Thermometer		Yes	Yes	Yes	Yes
Type of Controller		Mechanical	Mechanical	Mechanical	Mechanical
Noise Level	db(A)	45	45	45	45
Type of Cooling		Static	Static	Static	Static
Type of Defrost		Manual	Manual	Manual	Manual
Refrigerant		R600a	R290	R290	R290
Refrigerant Charge	g	55	85	105	110
Input Power	W	98	119	141	191
Voltage / Frequency	V/Hz	220-240/50	220-240/50	220-240/50	220-240/50
Energy Consumption	kWh/24h	1,32	1,48	1,93	2,39
Internal Dimension (WxDxH)	mm	600 x 510 x 576	890 x 510 x 576	1180 x 510 x 576	1430 x 510 x 576
External Dimension (WxDxH)	mm	740 x 650 x 885	1030 x 650 x 885	1320 x 650 x 885	1570 x 650 x 885
Packed Dimension (WxDxH)	mm	810 x 765 x 940	1100 x 765 x 940	1390 x 765 x 940	1640 x 765 x 940
40ft Container Load	pcs	84	64	50	42

Ice Cream Freezers



NIC500SCEB-P

Ice Cream Freezer

- Curved sliding lids with lock
- Digital thermometer
- Powder coated white steel inner liner
- Baskets
- Castors with brake



White coated steel inner liner



Digital thermometer



NIC100SCEB-I Ice Cream Freezer

- Curved sliding lid with lock
- Thermometer
- Divider system
- Powder coated white steel inner liner
- Castors with brake



NIC300SCEB-P Ice Cream Freezer

- Curved sliding lids with lock
- Digital thermometer
- Powder coated white steel inner liner
- Basket
- Castors with brake

MODEL		NIC100SCEB-I	NIC200SCEB-I	NIC300SCEB-P	NIC400SCEB-P	NIC500SCEB-P
Gross / Net Volume	l	130 / 115	185 / 138	286 / 218	388 / 298	475 / 367
Gross / Net Weight	kg	50 / 47	63 / 52	70 / 62	87 / 72	122 / 110
Climate Class		5	5	5	5	5
Temperature Range	°C	-24 to -14	-24 to -14	-24 to -14	-24 to -14	-24 to -14
Tempered glass		Yes	Yes	Yes	Yes	Yes
Lid Number & Type		1 flat sliding glass lid	2 curved sliding glass lids	2 curved sliding glass lids	2 curved sliding glass lids	2 curved sliding glass lids
Basket Number & Type		-	1 Wire basket, white	1 Wire basket, white	2 Wire baskets, white	2 Wire basket, white
Castors		4 wheels, 2 with brake	4 wheels, 2 with brake	4 wheels, 2 with brake	4 wheels, 2 with brake	4 wheels, 2 with brake
Exterior Finish		White	White	White	White	White
Interior Finish		White painted steel	White painted steel	White painted steel	White painted steel	White painted steel
Lock		Yes	Yes	Yes	Yes	Yes
Thermometer		Yes	Yes	Yes	Yes	Yes
Type of Controller		Mechanical	Mechanical	Mechanical	Mechanical	Mechanical
Noise Level	db(A)	41	45	45	45	45
Type of Cooling		Static	Static	Static	Static	Static
Type of Defrost		Manual	Manual	Manual	Manual	Manual
Refrigerant		R600a	R600a	R290	R290	R290
Refrigerant Charge	g	50	55	85	105	110
Input Power	W	105	98	119	141	191
Voltage / Frequency	V/Hz	220-240/50	220-240/50	220-240/50	220-240/50	220-240/50
Energy Consumption	kWh/24h	2,5	1,32	1,48	1,93	2,39
Internal Dimension (WxDxH)	mm	510 x 510 x 571	600 x 510 x 571	890 x 510 x 571	1180 x 510 x 571	1430 x 510 x 571
External Dimension (WxDxH)	mm	665 x 665 x 918	740 x 650 x 918	1030 x 650 x 918	1320 x 650 x 918	1570 x 650 x 918
Packed Dimension (WxDxH)	mm	700 x 700 x 970	810 x 765 x 960	1100 x 765 x 960	1390 x 765 x 960	1640 x 765 x 960
40ft Container Load	pcs	102	84	64	50	42

Various Freezers



CF77-I

Can Freezer

- Impulse freezer
- Fast pull-down of temperature
- Flip-flop lid
- Well suited for branding
- Strong castors



Strong castors



ST160-I

Ice Cream Freezer

- Flat hinged glass lid
- Thermometer
- Powder coated white steel inner liner
- Basket
- Castors with brake



MODEL		CF77-I	ST160-I
Gross / Net Volume	l	80 / 72	115 / 105
Gross / Net Weight	kg	33 / 29	43 / 35
Climate Class		4	4
Temperature Range	°C	-22 to -12	-24 to -14
Lid Number & Type		1 transparent acrylic flip-flop lid	1 hinged tempered glass lid
Basket Number & Type		-	1 Wire basket
Number of dividers	pcs	0	0
Interior Light		No	No
Canopy Type		-	-
Castors		4 castors, 1 lockable	4 double castors
Exterior Finish		White	White
Interior Finish		Powder coated steel	White painted steel
Lock		No	No
Thermometer		No	Yes
Type of Controller		Mechanical	Mechanical
Noise Level	db(A)	45	45
Type of Cooling		Static	Static
Type of Defrost		Manual	Manual
Refrigerant		R600a	R600a
Refrigerant Charge	g	40	60
Input Power	W	124	80
Voltage / Frequency	V/Hz	220-240/50	220-240/50
Energy Consumption	kWh/24h	1,1	0,7
Internal Dimension (WxDxH)	mm	454 x 454 x 440	435 x 435 x 755
External Dimension (WxDxH)	mm	567 x 567 x 830	550 x 550 x 870
Packed Dimension (WxDxH)	mm	580 x 580 x 880	655 x 600 x 955
40ft Container Load	pcs	238	156